



# MODUS PL 7000, wide body 1575mm, LED 865, body PE, opal PC cover, IP65, driver 1200mA

Code: PL7000L2W6ND EAN: **8596099001087** 























#### Mechanical properties

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes	Material housing:	Plastic
Suitable for wall mounting:	Yes	Suitable for surface mounting:	Yes
Rated ambient temperature (°C):	-10+45	Suitable for ceiling mounting:	Yes

# Light source

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	7700
System power (W):	53	Luminaire efficacy (lm/W):	145
Color temperature (K):	6500	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White	Energy efficiency class of the built-in lamp:	A++, A+, A (LED)

## Optical system

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

# Dimensions

Length (mm):	1575	Width (mm):	135
Height/depth (mm):	100	Built-in length (mm):	1100
Size version:	L	Weight (kg):	2,8

# **Electical properties**

Protection class:	1	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220240	Control gear included:	Yes
No dim function:	Yes		