

Busbar system with accessories

Without protection against accidental contact type PEN, PE and N, 400 A–1000 A

2



KSNS 417-498
400 A.



KSNS 1083-10181
1000 A.



KSNSV 410
Vertical PEN-bar, used in replacement of equipment in older enclosures where PEN- bar has not enough space.

Designation	ID No.	Dimensions			Weight kg/each
		Length	Width	Depth	
KSNSV 410	2CGX0 63120002	160	36	62	0,26

Designation	ID No.	Number of modules	Rated current	Length	Weight
		M *	A	mm	kg/m
KSNS 417	2CGX0 43320059	17	400	209	0.6
KSNS 420	2CGX0 43320192	20	400	333	0.6
KSNS 440 **	2CGX0 43320193	40	400	585	0.6
KSNS 443	2CGX0 43320052	43	400	569	0.6
KSNS 460	2CGX0 43320194	60	400	835	0.6
KSNS 463	2CGX0 43320053	63	400	809	0.6
KSNS 473	2CGX0 43320196	73	400	900	0.6
KSNS 498	2CGX0 43320190	98	400	1214	0.6
KSNS 498 KSIK	2CGX0 43320195	98	400	1266	0.6
KSNS 1083	2CGX0 43320162	83	1000	1079	1.6
KSNS 1098	2CGX0 43320169	98	1000	1212	1.6
KSNS 1098 KSIK	2CGX0 43320343	98	1000	1264	1.6
KSNS 10126	2CGX0 43320163	126	1000	1600	1.6
KSNS 10149	2CGX0 43320164	149	1000	1890	1.6
KSNS 10181	2CGX0 43320165	181	1000	2300	1.6

* One module M = 12.5 mm.

** KSNS 440 is used with SDC X48 and CDC X40.